

**ПАСПОРТ КАЧЕСТВА**  
**МАСЛО-КОМПОНЕНТ МК-12**  
**ТУ 19.20.29-011-70351853-2019**

**ANALYSIS REPORT No.20-123**

<b>Product:</b>	Lube oil
<b>Location:</b>	Kaliningrad
<b>Sample origin :</b>	Sample 1 x 1 L in plastic bottle, represented by Client
<b>Date of receipt:</b>	09.02.2020
<b>Date of testing:</b>	10.02.2020

Test	Method	Unit	Result
Kinematic Viscosity at 100 °C	ASTM D445	mm <sup>2</sup> /s	<b>3,950</b>
Kinematic Viscosity at 40 °C	ASTM D445	mm <sup>2</sup> /s	<b>18,87</b>
Viscosity Index	ASTM D2270	-	<b>106</b>
Recovered at 350 °C	ASTM D1160	% v/v.	<b>10,0</b>
Water content	ASTM D6304	% m/m	<b>0,021</b>
Sulphur content	ASTM D4294	% m/m	<b>0,283</b>
Pour Point	ASTM D97	°C	<b>minus 18</b>
Saponification Number	ISO 6293-2	mg KOH/g	<b>1,0</b>

**\*END OF REPORT\***